



## You need solutions FAST, eh? Count on Local Made-to-Order.

Project schedules are demanding. You need a partner you can trust. Count on Acuity Brands® to deliver the product you need — when, where and how you need it.

**Easy Ordering. Fast Shipping. Local Manufacturing.**



### How it works:

- Local Made-to-Order Stock orders received by Acuity Brands by noon<sup>1</sup> will ship on the 3rd day with a total Lead-time of 5 days for Ontario. Will call pick-up at the Central Canadian Distribution Centre (CCDC) in Thornhill, Ontario will be available for pick-up on the 3rd day.
- Canadian orders that are eligible will be routed to the Central Canadian Distribution Centre (CCDC) in Thornhill, Ontario. All other products are still available to order through the US LightQuick® Program.
- Local, dedicated customer care teams are ready to respond to opportunity needs, questions or issues.

<sup>1</sup>Quantities limited to 75 per SKU with 3 day manufacturing lead time.

Consult full spec sheet on [acuitybrands.ca](http://acuitybrands.ca) for complete product specifications.

---

**Products Now Configurable in Canada. No Borders to Cross.**

---

# Canada Local Made-to-Order Series



**CPHB**  
LED High Bay

Manufacturing Lead Time: 3 days  
Max. Qty: **75** units

**ORDERING INFORMATION** Specifications subject to change. **Example:** CPHB 24000LM SEF GCL MD 120 GZ10 40K 80CRI CPSBW LSXR6 HL DWH

Series	Lumens	Performance Package	Lens	Distribution	Voltage	Driver	Color Temperature
CPHB	12000LM	12,000 lumens	SEF Standard efficiency GCL Glare Control Lens	MD Medium ND Narrow WD Wide	MVOLT 120-277V 120 120V 208 208V 240 240V 277 277V	GZ10 0-10V dimming	40K 4000K 50K 5000K
	15000LM	15,000 lumens					
	18000LM	18,000 lumens					
	24000LM	24,000 lumens					
	30000LM	30,000 lumens					

Color Rendering Index	Options	Finish
80CRI 80 CRI	<p>WGX Wireguard installed IMP Integrated modular plug OCS RELOC® OnePass selectable cable 6' installed</p> <p><u>Cord Sets:</u> CPSBW 6' white damp location cord with straight blade plug (voltage will match fixture, 120V or 277V only) CPTLW 6' white damp location cord with twist-lock plug (voltage will match fixture; Not avail with 208V or 240V) CNPW 6' white cord, no plug CNP5CDW 6' white cord, 5 conductors (includes dimming leads)</p> <p>For additional cord set offerings, see table below.</p>	DWH Gloss white
<p><u>Individual Controls (LSXR):</u> LSXR6 360° integral high mount motion sensor with standard on/off operation LSXR6 HL 360° integral high mount motion sensor with high/low/off occupancy operation. For High/Low/(never off), bypass relay LSXR6 P 360° integral high mount motion sensor with on/off switching photocell LSXR6 ADC 360° integral high mount motion sensor with dimming &amp; switching photocell LSXR6 ANL 360° integral high mount motion sensor with High/Low (Off) occupancy dimming &amp; auto-dimming photocell</p> <p>*For 360° integral LOW MOUNT sensors, replace "6" in nomenclature with "10". For High Mount AISLEWAY sensors, replace "6" in nomenclature with "50". Ex: LSXR50 HL</p>		

Option Value Ordering Restrictions	
Option Value	Ordering Restrictions
Cord Sets	Must specify voltage on cord sets with plugs.
Individual Controls (LSXR)	Comes standard with SPD. This sensor configuration is suitable for minimum ambient temperature of 14°F (-10°C). Not available with other controls.
OCS	Dry Location listed only. Not available with Battery Options.

Accessories: Order as separate catalog number.	
<u>Wire guards:</u>	
WGCPHBSM	Wire guard for CPHB (12000LM - 18000LM)
WGCPHBMD	Wire guard for CPHB (24000LM - 30000LM)

### ADDITIONAL CORD SET OPTIONS

	Cord Set Nomenclature	Fixture Voltage	Description
12FT Options	CPSBW12FT	277	12', White cord, with NEMA 7-15 plug (277v, 15A, straight blade)
	CPTLW12FT	277	12', White cord, with NEMA L7-15 plug (277v, 15A, twist lock)
	CNPW12FT	Any	12', White cord, no plug, 3 conductors (BLK/WHT/GRN)
	CNP5CDW12FT	Any	12', White cord, no plug, 5 conductors for dimming - (BLK/WHT/GRN/PUR/GRY)
15FT Options	CPSBW15FT	277	15', White cord, with NEMA 7-15 plug (277v, 15A, straight blade)
	CPTLW15FT	277	15', White cord, with NEMA L7-15 plug (277v, 15A, twist lock)
	CNPW15FT	Any	15', White cord, no plug, 3 conductors (BLK/WHT/GRN)

\*CPHB will have additional cord set options available in April 2021. No additional lengths or configurations available at this time.